



ANSI D-RING COBRA® PRO STYLE

38 mm

Art.no.: FX38KVD

The synergistic hybrid of two standard components of safety industry hardware: the stainless steel D-ring and the ANSI COBRA® PRO STYLE - a buckle that meets the highest safety requirements. The unique construction prevents the D-ring from getting squeezed against the webbing and therefore guarantees easy handling.

When relieved the buckle can only be through pressing both clips at the same time. The locking mechanism makes one-sided locking of the buckle nearly impossible and is confirmed by a distinct 'clicking' sound.


This COBRA® buckle is marked according to the ANSI-standard with a guaranteed tensile strength of 15 kN. However, we guarantee 18 kN for the buckle and 22 kN for the D-ring and provide this informational data in the technical specifications accordingly. Tested in accordance to ANSI/ASSE, CSA and upon request NFPA.

use cases:

PPE, Fashion, air sports, tactical, equipment

Technical specifications

body	Material: aluminium Color: black Finish: ktl coated
clips	Material: brass Color: colorless Finish: polished
bar	Material: stainless steel Color: colorless Finish: polished

d-ring	Material: stainless steel
Breaking load tensile strength	18 kN
Weight	139 g
Recomm. webbing width	38 mm
Recomm. webbing width female part	38 mm
Outer dimension length	69 mm
Outer dimension width	58 mm
Outer dimension depth	14 mm
Technical design male part	adjustable
Technical design female part	non adjustable with integrated D-ring
Single piece tested	Yes
Country of origin	Austria
 Patented	
Standards	ANSI/ASSE Z359.12-2019, CSA Z259.12-2016 Class I, EN358:2018-11 (partial)

