

## ANSI D-RING COBRA® PRO STYLE

45 mm

Art.no.: FX45KVD



The synergistic hybrid of two standard components of safety industry hardware: the stainless steel D-ring and the ANSI COBRA® PRO STYLE - a buckle that meets the highest safety requirements. The unique construction prevents the D-ring from getting squeezed against the webbing and therefore guarantees easy handling.

When relieved the buckle can only be through pressing both clips at the same time. The locking mechanism makes one-sided locking of the buckle nearly impossible and is confirmed by a distinct 'clicking' sound.


This COBRA® buckle is marked according to the ANSI-standard with a guaranteed tensile strength of 15 kN. However, we guarantee 18 kN for the buckle and 22 kN for the D-ring and provide this informational data in the technical specifications accordingly. Tested in accordance to ANSI/ASSE, CSA and upon request NFPA.

### use cases:

PPE, Fashion, air sports, tactical, equipment

## Technical specifications

<b>body</b>	<b>Material:</b> aluminium <b>Color:</b> black <b>Finish:</b> ktl coated
<b>clips</b>	<b>Material:</b> brass <b>Color:</b> colorless <b>Finish:</b> polished
<b>bar</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished

<b>d-ring</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>Breaking load tensile strength</b>	18 kN
<b>Breaking load D-Ring</b>	22 kN
<b>Weight</b>	149 g
<b>Recomm. webbing width</b>	45 mm
<b>Recomm. webbing width female part</b>	45 mm
<b>Outer dimension length</b>	68 mm
<b>Outer dimension width</b>	64 mm
<b>Outer dimension depth</b>	14 mm
<b>Technical design male part</b>	adjustable
<b>Technical design female part</b>	non adjustable with integrated D-ring
<b>Single piece tested</b>	Yes
<b>Country of origin</b>	Austria
 <b>Patented</b>	
<b>Standards</b>	ANSI/ASSE Z359.12-2019, CSA Z259.12-2016 Class I, EN358:2018-11 (partial)

