

2-SLOT-FRAME BUCKLE

25 mm

Art.no.: DY25AFS



The next generation of ergonomically arched 2-slot-frame buckles impresses with a completely redesigned look and maximum functionality. Thanks to the embossed batch number, each buckle can be reliably traced.

The new models retain all proven technical properties of their predecessors. These include high tensile strength for maximum safety and load capacity, as well as excellent corrosion resistance in accordance with EN ISO 9227.

2-slot frame buckle DY25AFS must be used in combination with matching frame buckle DY25_FB only.

use cases:

PPE, Fashion, air sports, tactical, equipment

Technical specifications

BODY	Material: aluminium Color: colorless Finish: polished
BREAKING LOAD TENSILE STRENGTH	7.5 kN
BREAKING LOAD LOOP CONFIGURATION	15 kN
WEIGHT	9 g
RECOMM. WEBBING WIDTH	25 mm
OUTER DIMENSION LENGTH	30 mm
OUTER DIMENSION WIDTH	40 mm
OUTER DIMENSION DEPTH	4 mm
COUNTRY OF ORIGIN	Austria

STANDARDS	EN ISO 9227
 <p>The image shows a silver-colored metal webbing buckle. It has a rectangular shape with rounded corners and a central horizontal slot. The buckle is embossed with the text "made in Austria" at the top, "webbing" in the center, and "AUSTRIALPIN" at the bottom.</p>	