

## COBRA® SPECIAL DESIGNS

### ANCHOR COBRA OUL, OPENS UNDER LOAD

**25 mm, 180 degrees rotatable**

Art.no.: FO00K180-XL+L



Originally designed for Picatinny Arsenal as a conceptual MRAP anchoring system, the COBRA® ANCHOR OUL bolts (1/2 inch hardware) onto any solid surface. The female buckle portion of the anchor can be tilted by up 180 degrees offering a wide angle of use and variability. A COBRA® OUL (9 kN) male part is then affixed to any gear, kit, or package whereby it can be securely clipped in and stowed away for rapid, easy, safe access. This is great for vehicular and aircraft stowage applications as well as for applications where load bearing “clip and go” storage options are required. Not suitable as PPE!

#### use cases:

tactical, equipment

## Technical specifications

<b>BODY</b>	<b>Material:</b> aluminium <b>Color:</b> black <b>Finish:</b> ktl-coated
<b>CLIPS</b>	<b>Material:</b> brass <b>Color:</b> colorless <b>Finish:</b> polished
<b>PLATE</b>	<b>Material:</b> aluminium <b>Color:</b> black <b>Finish:</b> ktl-coated
<b>AXLE</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>BREAKING LOAD TENSILE STRENGTH</b>	9 kN
<b>BREAKING LOAD LOOP CONFIGURATION</b>	18 kN
<b>WEIGHT</b>	104 g
<b>OUTER DIMENSION LENGTH</b>	37 mm



