

COBRA OUL 9 KN OPEN UNDER LOAD

25 mm

Art.no.: FO25KVF



Unlike all other COBRA® Quick Release buckles, the COBRA® OUL can be opened under load. Therefore it can for example be used to secure cargo or wherever items have to be immediately accessible. This is why it can't be used as a personal protective equipment. However, the breaking load is still the same as the one of the non-OUL models. A COBRA® OUL can not be combined with a regular COBRA®, but a COBRA® OUL can be combined any other COBRA® OUL of the same type.


The COBRA® OUL (9 kN) can be opened under load. In combination with a fitting webbing, the minimum guaranteed load capacity is 18 kN in loop configuration. Not suitable as PPE!

use cases:

Fashion, tactical, equipment

Technical specifications

BODY	Material: aluminium Color: black Finish: ktl-coated
CLIPS	Material: brass Color: colorless Finish: polished
BAR	Material: stainless steel Color: colorless Finish: polished
BREAKING LOAD TENSILE STRENGTH	9 kN
BREAKING LOAD LOOP CONFIGURATION	18 kN
WEIGHT	53 g
RECOMM. WEBBING WIDTH MALE PART	25 mm

RECOMM. WEBBING WIDTH FEMALE PART	25 mm
SLOT WIDTH MALE PART	12 mm
SLOT WIDTH FEMALE PART	6 mm
OUTER DIMENSION LENGTH	58 mm
OUTER DIMENSION WIDTH	40 mm
OUTER DIMENSION DEPTH	10 mm
TECHNICAL DESIGN MALE PART	adjustable
TECHNICAL DESIGN FEMALE PART	non adjustable
SIZE OF CLIPS	standard
COUNTRY OF ORIGIN	Austria
 Patented	
STANDARDS	EN ISO 9227



