

## OVALO

### SCREWLOCK WITH BRASS SLEEVE

**polished**

Art.no.: KA13A



OVALO – the yogi among the carabiners: Its oval form benefits the optimal position of the carabiner along its transverse axis and thus reduces dangerous transverse loading in every situation. Additionally, the round profile prevents the build-up of sharp edges due to rope friction and allows a fluid rope management. The OVALO screwlock carabiner with smooth-running, corrosion-resistant brass sleeve. Thanks to a special milling at the thread, the screwlock has a unique self-cleaning process.

#### use cases:

sports climbing, ice climbing, mountain sports, canyoning, PPE

## Technical specifications

|   |  |
|---|--|
| <b>BODY</b>   | <b>Material:</b> aluminium<br><b>Color:</b> colorless<br><b>Finish:</b> polished |
| <b>GATE</b>   | <b>Material:</b> aluminium<br><b>Color:</b> colorless<br><b>Finish:</b> polished |
| <b>SLEEVE</b>                                       | <b>Material:</b> brass<br><b>Color:</b> colorless<br><b>Finish:</b> polished     |
| <b>WEIGHT</b>                                       | 71 g   |
| <b>LENGTH</b>                                       | 105 mm   |
| <b>WIDTH</b>  | 58 mm  |
| <b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b> | 24 kN  |
| <b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>         | 10 kN  |
| <b>MIN. BREAKING LOAD WITH OPEN GATE</b>            | 7 kN   |

|                          |  |
|--------------------------|--|
| <b>LOCK</b>              | screw lock                                   |
| <b>GATE OPENING</b>      | 19 mm  |
| <b>COUNTRY OF ORIGIN</b> | Austria                                      |
| <b>EAN CODE</b>          | 9006381013623                                |
| <b>STANDARDS</b>         | EN 12275:2013 (B), EN 362:2004 (B), UIAA 121 |

