

# OVALO

## GI SCREWLOCK WITH BRASS SLEEVE

aluminium, anodized  
Art.no.: KA13B-G-GI




OVALO - the yogi among the carabiners: Its oval form benefits the optimal position of the carabiner along its transverse axis and thus reduces dangerous transverse loading in every situation. Additionally, the round profile prevents the build-up of sharp edges due to rope friction and allows a fluid rope management. The OVALO screwlock carabiner with smooth-running, corrosion-resistant brass sleeve. Thanks to a special milling at the thread, the screwlock has a unique self-cleaning process. Special features of the OVALO GI screwlock are its red visual safety band [Gate Red] and a unique identification number [ID].

**use cases:**  
sports climbing, ice climbing, mountain sports, canyoning, PPE

### Technical specifications

BODY	<b>Material:</b> aluminium <b>Color:</b> anthracite <b>Finish:</b> anodized
GATE	<b>Material:</b> aluminium <b>Color:</b> colorless <b>Finish:</b> polished
SLEEVE	<b>Material:</b> brass <b>Color:</b> colorless <b>Finish:</b> polished
WEIGHT	71 g

<b>LENGTH</b>	105 mm
<b>WIDTH</b>	56 mm
<b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b>	24 kN
<b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>	10 kN
<b>MIN. BREAKING LOAD WITH OPEN GATE</b>	7 kN
<b>LOCK</b>	screwlock
<b>FEATURES</b>	ID+GateRed
<b>GATE OPENING</b>	19 mm
<b>COUNTRY OF ORIGIN</b>	Austria
<b>EAN CODE</b>	9006381013661
<b>COLOR VARIATIONS</b>	 <p>azure [Art.no.: KA13B-B-GI]</p> <p>red [Art.no.: KA13B-R-GI]</p> <p>black [Art.no.: KA13B-Z-GI]</p>
<b>STANDARDS</b>	EN 12275:2013 (B), EN 362:2004 (B), UIAA 121



## UNIQUE IDENTIFICATION NUMBER (ID)



ID# KA 01234

letter 1 and 2 of  
article no. /  
unique number

 XX/XXXX

month/year  
of production

EN 362-B

additional  
norm marking