

## OVALO OVALOCK

**push & open**

Art.no.: KA65B-N



The intuitive lock only allows two options: open or closed. The bar is made out of molded reinforced fibre glass plastic and effectively separates the carabiner into two distinct sections - thus eliminating the dangers of cross loading. No screwing, no weird handling: just push and open!

### use cases:

sports climbing, ice climbing, mountain sports, canyoning, PPE

## Technical specifications

|                                                     |                                                                                     |
|-----------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>BODY</b>                                         | <b>Material:</b> aluminium<br><b>Color:</b> bright green<br><b>Finish:</b> anodized |
| <b>GATE</b>                                         | <b>Material:</b> aluminium<br><b>Color:</b> colorless<br><b>Finish:</b> polished    |
| <b>LOCK</b>                                         | <b>Material:</b> polymer<br><b>Color:</b> black                                     |
| <b>WEIGHT</b>                                       | 70 g                                                                                |
| <b>LENGTH</b>                                       | 105 mm                                                                              |
| <b>WIDTH</b>                                        | 65 mm                                                                               |
| <b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b> | 24 kN                                                                               |
| <b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>         | 10 kN                                                                               |
| <b>MIN. BREAKING LOAD WITH OPEN GATE</b>            | 7 kN                                                                                |
| <b>LOCK</b>                                         | Ovalock                                                                             |

|                                                                                     |                                                                                                                                                                                                                                 |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>GATE OPENING</b>                                                                 | 18 mm                                                                                                                                                                                                                           |
| <b>COUNTRY OF ORIGIN</b>                                                            | Austria                                                                                                                                                                                                                         |
| <b>EAN CODE</b>                                                                     | 9006381306541                                                                                                                                                                                                                   |
| <b>COLOR VARIATIONS</b>                                                             |  yellow [Art.no.: KA65B-Y]<br> matte black [Art.no.: KA65B-X] |
| <b>STANDARDS</b>                                                                    | EN 12275:2013 (B), EN 362:2004 (B), UIAA 121                                                                                                                                                                                    |
|  |                                                                                                                                                                                                                                 |