

## FERR.DA

### SCREWLOCK WITH BRASS SLEEVE

**stainless steel 40 kN**

Art.no.: NW13A



The strong FERR.DA stainless steel carabiner is a reliable connector on the vertical. Its asymmetrical D-shape offers plenty of space for numerous connecting elements and complex rope structures.

The FERR.DA screwgate carabiner is equipped with a smooth-running brass sleeve. The special milling in the thread allows the locking mechanism to clean itself.

With an impressive breaking load of 40 kN, the carabiner guarantees maximum stability and safety. The round cross-section ensures gentle rope guidance and reduces abrasion even under dynamic loads.

Manufactured in Austria from high-quality stainless steel, this carabiner features outstanding corrosion resistance and durability. It is a reliable partner for use in extreme conditions.

#### use cases:

PPE, equipment

## Technical specifications

<b>BODY</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>GATE</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>SLEEVE</b>	<b>Material:</b> brass <b>Color:</b> colorless <b>Finish:</b> polished
<b>WEIGHT</b>	242 g
<b>LENGTH</b>	113 mm
<b>WIDTH</b>	70 mm

<b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b>	40 kN
<b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>	16 kN
<b>MIN. BREAKING LOAD WITH OPEN GATE</b>	12 kN
<b>LOCK</b>	screwlock
<b>GATE OPENING</b>	25 mm
<b>COUNTRY OF ORIGIN</b>	Austria
<b>EAN CODE</b>	9006381029235
<b>STANDARDS</b>	EN 12275:2013 (B), EN 362:2004 (M), UIAA 121
	