

## FERR.DA TWISTLOCK

**stainless steel 40 kN**

Art.no.: NW22A



The strong FERR.DA stainless steel carabiner is a reliable connector for vertical use. Its asymmetrical D-shape offers plenty of space for numerous connecting elements and complex rope structures.

In the 2-way autolock version, it strikes a great balance between safety and easy use. The carabiner can be opened easily by twisting the sleeve and pushing in the gate. Once the gate is released, it locks automatically.

With an impressive breaking load of 40 kN, the carabiner guarantees maximum stability and safety. The round cross-section ensures gentle rope guidance and reduces abrasion even under dynamic loads.

Manufactured in Austria from high-quality stainless steel with an aluminium sleeve, this carabiner features outstanding corrosion resistance and durability. It is a reliable partner for use in extreme conditions.

### use cases:

PPE, equipment

## Technical specifications

<b>BODY</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>GATE</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>SLEEVE</b>	<b>Material:</b> aluminium <b>Color:</b> azure <b>Finish:</b> anodized
<b>WEIGHT</b>	237 g
<b>LENGTH</b>	113 mm
<b>WIDTH</b>	70 mm

<b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b>	40 kN
<b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>	16 kN
<b>MIN. BREAKING LOAD WITH OPEN GATE</b>	12 kN
<b>LOCK</b>	2-way autolock
<b>GATE OPENING</b>	24 mm
<b>COUNTRY OF ORIGIN</b>	Austria
<b>EAN CODE</b>	9006381029204
<b>STANDARDS</b>	EN 12275:2013 (B), EN 362:2004 (M), UIAA 121

