

## FERR.DA

### ID TRIPLELOCK WITH BRASS SLEEVE

**stainless steel 40 kN, individual numbering**

Art.no.: NW33A-ID



The strong FERR.DA stainless steel carabiner is a reliable connector on the vertical. Its asymmetrical D-shape offers plenty of space for numerous connecting elements and complex rope structures.

This 3-way autolock model offers a high degree of safety. The triplelock carabiner can only be opened by performing three successive actions: Lift the sleeve, twist it, and push in the gate. This makes unintentional opening virtually impossible, even in the event of strong movement, friction or snagging. Once the gate is released, it automatically locks.

With an impressive breaking load of 40 kN, the carabiner guarantees maximum stability and safety. The round cross-section ensures gentle rope guidance and reduces abrasion even under dynamic loads.

Manufactured in Austria from high-quality stainless steel with a brass sleeve, this carabiner features outstanding corrosion resistance and durability. It is a reliable partner for use in extreme conditions.

#### use cases:

PPE, equipment

## Technical specifications

<b>BODY</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>GATE</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>SLEEVE</b>	<b>Material:</b> brass <b>Color:</b> colorless <b>Finish:</b> polished
<b>WEIGHT</b>	288 g
<b>LENGTH</b>	113 mm

<b>WIDTH</b>	70 mm
<b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b>	40 kN
<b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>	16 kN
<b>MIN. BREAKING LOAD WITH OPEN GATE</b>	12 kN
<b>LOCK</b>	3-way autolock
<b>FEATURES</b>	ID
<b>GATE OPENING</b>	24 mm
<b>COUNTRY OF ORIGIN</b>	Austria
<b>EAN CODE</b>	9006381030361
<b>STANDARDS</b>	EN 12275:2013 (B), EN 362:2004 (M), UIAA 121



### UNIQUE IDENTIFICATION NUMBER (ID)

