

FERR.DA TRIPLELOCK+ SAFELOCK

stainless steel 40 kN

Art.no.: NW52A



The strong FERR.DA stainless steel carabiner is a reliable connector on the vertical. Its asymmetrical D-shape offers plenty of space for numerous connecting elements and complex rope structures.

This 3-way autolock+ safelock model ensures extra secure locking. It can be opened from the normal closed position in 3 steps: Lift the sleeve, twist it, and push in the gate. The additional safelock function reliably prevents unintentional opening. As with all autolocks, this carabiner locks automatically when the gate is released.

With an impressive breaking load of 40 kN, the carabiner guarantees maximum stability and safety. The round cross-section ensures gentle rope guidance and reduces abrasion even under dynamic loads.

Manufactured in Austria from high-quality stainless steel, this carabiner features outstanding corrosion resistance and durability. It is a reliable partner for use in extreme conditions.

use cases:

PPE, equipment

Technical specifications

BODY	Material: stainless steel Color: colorless Finish: polished
GATE	Material: stainless steel Color: colorless Finish: polished
SLEEVE	Material: aluminium Color: azure Finish: anodized
WEIGHT	235 g
LENGTH	113 mm

WIDTH	70 mm
MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION	40 kN
MIN. BREAKING LOAD IN THE MINOR AXIS	16 kN
MIN. BREAKING LOAD WITH OPEN GATE	12 kN
LOCK	3-way+ autolock
GATE OPENING	24 mm
COUNTRY OF ORIGIN	Austria
EAN CODE	9006381029228
STANDARDS	EN 12275:2013 (B), EN 362:2004 (M), UIAA 121

