

## ELEVEN

### QUICKDRAW SET 12 CM

**snapgate, anodized, with Tanga**

Art.no.: QE11K-VYT



Our strongest set, specifically made for sport climbing. The 1.1 tons gate-open-breaking load and a large diameter allow rope-friendly and fearless falling. It comes with the quickdraw-TANGA, a webbing protection that keeps the carabiner in place, and an extra wide polyamide-sling. ELEVEN quickdraw with two snapgate carabiners.

#### use cases:

sports climbing, mountain sports

## Technical specifications

|                                                     |                                                                                  |
|-----------------------------------------------------|----------------------------------------------------------------------------------|
| <b>CARABINER</b>                                    | <b>Material:</b> aluminium<br><b>Color:</b> colorless<br><b>Finish:</b> anodized |
| <b>CARABINER</b>                                    | <b>Material:</b> aluminium<br><b>Color:</b> yellow<br><b>Finish:</b> anodized    |
| <b>SLING</b>                                        | <b>Material:</b> polyamide<br><b>Color:</b> white                                |
| <b>TANGA</b>                                        | <b>Material:</b> polymer<br><b>Color:</b> black                                  |
| <b>WEIGHT</b>                                       | 117 g                                                                            |
| <b>LENGTH OF SLING</b>                              | 12 cm                                                                            |
| <b>WIDTH</b>                                        | 59 mm                                                                            |
| <b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b> | 25 kN                                                                            |
| <b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>         | 8 kN                                                                             |

|                                          |                                            |
|------------------------------------------|--------------------------------------------|
| <b>MIN. BREAKING LOAD WITH OPEN GATE</b> | 11 kN                                      |
| <b>BREAKING LOAD</b>                     | 22 kN                                      |
| <b>LOCK</b>                              | snapgate                                   |
| <b>GATE OPENING</b>                      | 19 mm, 19 mm                               |
| <b>COUNTRY OF ORIGIN</b>                 | Austria                                    |
| <b>EAN CODE</b>                          | 9006381009039                              |
| <b>SIZE VARIATIONS</b>                   | [Art.no.: QE20K-VYT]                       |
| <b>STANDARDS</b>                         | , EN 12275:2013 (B), UIAA 122, EN 566:2017 |

