

## DYNA.MIT

### CORD WITH DYNEEMA CORE

**22 kN**

Art.no.: ZS53RY-B



530 cm long, blue cord with extra high breaking strength of 22 kN (single strand). Simplifying material handling while in the mountains.

+ 6 mm diameter cord with dyneema-core and polyester sheath combine for optimal performance of a sewn sling (universal functionality) and cord (can be knotted without difficulty).

+ The color concept blue, green, red, black simplifies material handling, organizes the belay, makes trading off material easy and clarifies the setup of rescue systems.

+ The adjusted lengths allow you to select what you want as quickly as possible (black: simple, red/grey: double, blue: triple).

+ The ends are sewn at 5 cm to minimize slipping of the sheath with respect to the smooth dyneema core, and to allow for the correct knot placement.

The carabiner shown in figure 2 is not included in the delivery.

#### use cases:

mountain sports

## Technical specifications

|                      |                                                   |
|----------------------|---------------------------------------------------|
| <b>SHEATH</b>        | <b>Material:</b> polyester<br><b>Color:</b> azure |
| <b>CORE</b>          | <b>Material:</b> dyneema<br><b>Color:</b> yellow  |
| <b>BREAKING LOAD</b> | 22 kN                                             |
| <b>LENGTH</b>        | 5.3 m                                             |
| <b>DIAMETER</b>      | 6 mm                                              |
| <b>WEIGHT</b>        | 135 g                                             |

|                          |                                                                   |
|--------------------------|-------------------------------------------------------------------|
| <b>COUNTRY OF ORIGIN</b> | Czech Republic                                                    |
| <b>EAN CODE</b>          | 9006381695324                                                     |
| <b>SIZE VARIATIONS</b>   | [Art.no.: ZS17RY-Z]<br>[Art.no.: ZS29RY-G]<br>[Art.no.: ZS29RY-R] |
| <b>STANDARDS</b>         | EN 564:2015                                                       |

